

ACCESSORI

■ STANDARD □ OPTIONAL

DESCRIPTION	REX 30 GOLD	REX 30 GOLD + T	REX 25 + TP	REX 30 GOLD F	REX GOLD 30 +TF	REX GOLD 25 +TPF	
standard Color BLUE RAL 5005 and SILVER RAL 7040	■	■	■	■	■	■	
Nr. 1 Standard platform with electrostatics galvanized smooth staves	■	■	■	■	■	■	
Max. travel 4.100 mm.	■	■	■	■	■	■	
Flanged scissor				■	■	■	
Nr. 2 bases for pit fixing	■	■	■	■	■	■	
Nr. 2 Lifting Cylinders	■	■	■	■	■	■	
Nr. 2 "Dead man present" push button board with key at the floors	■	■	■	■	■	■	
Security control module for sensors and safety locks	■	■	■	■	■	■	
N. 2 Electromagnetic sensors or N. 2 safety mechanical locks	■	■	■	■	■	■	
Nr. 1 hydraulic pump with motor	■	■	■	■	■	■	
Nr. 1 Electrical panel board	■	■	■	■	■	■	
standard power supply 230-400 V/3Ph/50 Hz- 460 V/3Ph/60 Hz	■	■	■	■	■	■	
N. 2 stopping wheels L = 745 mm	■	■	■	■	■	■	
2 stops	■	■	■	■	■	■	
Transittable roof 3.000 Kg max - not suitable for lifting vehicles		■			■		Roof transittability: max. 3000 kg. (Not suitable for lifting vehicle)
Tileable roof in smooth metal sheet with tray of 30 mm. for lining			■			■	Roof transittability: max. 3000 kg. (Not suitable for lifting vehicle) Tiles weight allowed max 70 Kg / m2 ; Pit has been modified for tile thickness
Nylon package	■	■	■	■	■	■	
Anchors screws	■	■	■	■	■	■	
Non standard platform	□	□	□	□	□	□	
Hot dip galvanized staves for standard platform	□	□	□	□	□	□	
Hot dip galvanized staves for non standard platform	□	□	□	□	□	□	
Tileable platform predisposition	□			□			Tiles weight max 70 Kg /m2; Pit has been modified for tiles thickness. Add bearing wheels kit for intensive use
Loading capacity up to 4.000 Kg	□	□	□	□	□	□	Mandatory with roof version
bearing wheel for intensive use	□	□	□	□	□	□	advised for 10 cycles a day and for roof versions
Additional stop (third stop)	□	□	□	□	□	□	
additional push button board	□	□	□	□	□	□	
residential design push button board	□	□	□	□	□	□	
stainless steel push button board	□	□	□	□	□	□	
additional electromagnetic sensor	□	□	□	□	□	□	
Additional mechanical safety lock	□	□	□	□	□	□	Control for manual doors
Predisposition for electromechanical safety lock Kronenberg or Prudhomme	□	□	□	□	□	□	Control for manual doors
Outside pulse call for each push button board	□	□	□	□	□	□	Applicable on a enclosed shaft
Automatic repositioning platform at home position (just with pulse call option)	□	□	□	□	□	□	Applicable on a enclosed shaft
Automatic repositioning platform in case of fire	□	□	□	□	□	□	Applicable on a enclosed shaft
Receiver for remote control use	□	□	□	□	□	□	Operational distance max. 5 m
Transmitter for remote control use	□	□	□	□	□	□	Operational distance max. 5 m
Flashing light	□	□	□	□	□	□	
Siren	□	□	□	□	□	□	
Traffic light (two colors)	□	□	□	□	□	□	
Traffic light (two colors) residential design	□	□	□	□	□	□	

