

ACCESSORI

■ STANDARD □ OPTIONAL

DESCRIPTION	MONO 7,5	MONO 10	MONO 15	NOTE
standard Color BLUE RAL 5005 and SILVER RAL 7040	■	■	■	
Nr. 2 columns with cylinders and tooth rack	■	■	■	
Nr. 1 checker plate platform	■	■	■	
Nr. 2 "Dead man present" push button board with key at the floors IP 65	■	■	■	
Security control module for sensors and safety locks	■	■	■	
N. 2 Electromagnetic sensors or N. 2 safety mechanical locks	■	■	■	
Nr. 1 hydraulic pump with motor	■	■	■	
Nr. 1 Electrical panel board	■	■	■	
standard power supply 230-400 V/3Ph/50 Hz- 460 V/3Ph/60 Hz	■	■	■	
Nr. 1 slowing kit	■	■	■	
N. 1 protection for column	■	■	■	
Standard travel up to 4 mt.	■	■	■	
N. 2 stops	■	■	■	
Mechanical loking devices each level	■	■	■	
Nylon packaging	■	■	■	
Anchoring screws	■	■	■	
Emergency push button with key for pit access	□	□	□	
reverse guides	□	□	□	
Adjustable height at the floor: +/-50 mm. (per floor)	□	□	□	
Travel over 4 mt. up to 10 mt (each 500 mm.)	□	□	□	
Travel over 10 mt. up to 17 mt (each 500 mm.)	□	□	□	
Additional cost for non standard platform	□	□	□	
Width sizes of platform up to 3.000 mm. on request	□	□	□	
Additional stop (3rd stop)	□	□	□	
Further additional stop	□	□	□	Applicable up to max 6 stops
Junction for columns splitted in two or more pieces	□	□	□	Verify accessibility to the shaft
Additional push button board	□	□	□	
Additional push button board - residential type	□	□	□	
Stainless steel push button board	□	□	□	
Security control module for sensors and safety locks	□	□	□	
Additional magnetic sensor	□	□	□	
additional mechanical locking stopper	□	□	□	Control for manual doors
Predisposition for electromechanical safety lock Kronenberg or Prudhomme	□	□	□	Control for manual doors
Outside pulse call for each push button board	□	□	□	Applicable on a enclosed shaft
Automatic repositioning platform at home position (just with pulse call option)	□	□	□	Applicable on a enclosed shaft
Automatic repositioning platform in case of fire	□	□	□	Applicable on a enclosed shaft
Receiver for remote control use	□	□	□	Operational distance max. 5 m
Transmitter for remote control use	□	□	□	Operational distance max. 5 m
Flashing light	□	□	□	
Siren	□	□	□	
Trafic light (two colors)	□	□	□	
Trafic light (two colors) residential design	□	□	□	
Soft Starter	□	□	□	
Hydraulic pump with low acoustic emission	□	□	□	On request
manual pump for emergency descent maneuver	□	□	□	
Back up battery for auxiliaries circuits	□	□	□	Allows the emergency descent with platform not hanged to the floor
Waterproof galvanized cover for control unit for outdoor installation	□	□	□	

Set of Nr. 2 cylinders underneath the platform for stabilizing position	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Installation underneath the platform
Nr. 1 fix handrail H=1.200 mm. (per meter)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Nr. 1 removable handrail H = 1.200 mm (per meter)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Photocells barriers for doors area control H= 150 mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Photocells barriers for doors area control H= 300 mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Laser scanner	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Monophase power supply 220V/1Ph/50-60Hz	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Non standard power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	On request
Non standard color	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Interpon + powered coated painting (platform, columns and guides)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Interpon + powered coated painting over 4 mt. (each 500 mm)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Interpon + powered coated painting for non standard platform	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Hot dip galvanization (Platform, columns and guides)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Platform, columns and guides
Interpon + powered coated painting over 4 mt. (each 500 mm)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Interpon + powered coated painting for non standard platform	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Hot dip galvanization N.. 1 element fix protection for column	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Column on pallet	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Platform on pallet	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Control panel crate	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	